


LenelS2 Supervised Input Application Blade

Overview

LenelS2™ Supervised Input Application Blade is an interface board with eight input points to support a wide range of devices. The inputs support normally open, normally closed, supervised and non-supervised circuits. Compatible devices include buttons, door contacts, motion detectors, beam detectors, power supply monitoring points, burglar and alarm panel points and more.

Up to seven LenelS2 Application Blades in any combination can be supported by an Network Node. LenelS2 Application Blades are easy to install – Nodes automatically recognize and address them without jumpers or switches. Power and communications are delivered to every LenelS2 Application Blade via a ribbon cable bus.



Up to seven LenelS2 Application Blades in any combination can be supported by an Network Node.


Key Features

Inputs

- **Device Support:** Supports buttons, door contacts, motion detectors, beam detectors, power supply monitoring points, burglar and alarm panel points and more
- **Input Configuration:** Includes eight inputs configurable to normally open, normally closed, supervised and non-supervised circuits

System

- **Automatic Discovery:** Automatically connects to Network Node without jumpers or switches
- **Hardware Compatibility:** Fits available blade slots in NetBox™, NetBox VRx Quatro, NetBox VR Quatro, Network Node, Network Node VRx and Network Node VR hardware



Schematic only. Not a network diagram.

Specifications – LeleS2 Supervised Input Application Blade

Access Control		Cabling Requirements	
Supervised Inputs	8	Supervised Input Cable	Twisted, shielded 22 AWG Belden #9462
Input Supervision	Quad State (Open / Short / Normal / Alarm) Resistors value = 1K	Max Supervised Input Cable Distance	2000 ft (610 m)
Selection per Input	Dual Resistor / Single Series Resistor / Single Parallel Resistor / Unsupervised	Part Numbers	
Input Circuit Types	C / NO / NC	S2-INP	Supervised input application extension blade with 8 inputs
General			
Dimensions (H, W, D)	7.5 in x 4.0 in x 0.83 in (191 mm x 102 mm x 21.1 mm)		
Weight	4.5 oz (127 g)		
Operating Temperature	32°F – 95°F (0°C – 35°C)		
Storage Temperature	-4° – 158°F (-20° – 70°C)		
Operating Environment	Humidity 85%, non-condensing 35° C		
BTU Maximum	20 per hour		
Regulatory Approvals	UL, CE, RoHS		
Warranty	2 years, hardware		



For more information, please visit lenel2.com.

Specifications subject to change without notice.

© 2024 Honeywell International Inc. All rights reserved.
All trademarks are the property of their respective owners.